

Soft start - soft stop units, from 17A to 590A
Many function and communication protocol
Line voltage 220VAC to 415VAC

Bộ khởi động và dừng mềm, từ 17A đến 590A
Tích hợp nhiều chức năng và giao thức truyền thông
Điện áp cung cấp: 220VAC đến 415VAC



Unit price (incl.VAT) in VND

For standard applications

| Motor | | | Starter 230/415V - 50/60Hz | Reference | Unit Price |
|-----------------|------|------|----------------------------|-----------|-------------|
| Motor power (1) | | | Nominal current (IcL) (2) | | |
| 230V | 400V | 440V | | | |
| kW | kW | kW | A | | |
| 4 | 7.5 | 7.5 | 17 | ATS22D17Q | 17,556,000 |
| 7.5 | 15 | 15 | 32 | ATS22D32Q | 19,866,000 |
| 11 | 22 | 22 | 47 | ATS22D47Q | 22,869,000 |
| 15 | 30 | 30 | 62 | ATS22D62Q | 24,838,000 |
| 18.5 | 37 | 37 | 75 | ATS22D75Q | 27,027,000 |
| 22 | 45 | 45 | 88 | ATS22D88Q | 29,568,000 |
| 30 | 55 | 55 | 110 | ATS22C11Q | 39,622,000 |
| 37 | 75 | 75 | 140 | ATS22C14Q | 44,352,000 |
| 45 | 90 | 90 | 170 | ATS22C17Q | 45,397,000 |
| 55 | 110 | 110 | 210 | ATS22C21Q | 64,680,000 |
| 75 | 132 | 132 | 250 | ATS22C25Q | 73,689,000 |
| 90 | 160 | 160 | 320 | ATS22C32Q | 85,129,000 |
| 110 | 220 | 220 | 410 | ATS22C41Q | 108,460,000 |
| 132 | 250 | 250 | 480 | ATS22C48Q | 125,895,000 |
| 160 | 315 | 355 | 590 | ATS22C59Q | 133,287,000 |

| Dimensions (on mm) | width x height x depth |
|--------------------|------------------------|
| Size A: | 130 x 265 x 169 |
| Size B: | 145 x 295 x 207 |
| Size C: | 150 x 356 x 229 |
| Size D: | 206 x 425 x 299 |
| Size E: | 304 x 455 x 340 |

| Supply voltage | | Three-phase 208...600V (1) | Three-phase 230...440V |
|------------------------------|-----------------------------|--|---------------------------|
| Protection | Degree of protection | IP 20 : For ATS22D17...C11 IP 00 : For ATS22C14...C59 (protection of terminais available as an option) | |
| Drive | Motor thermal protection | Class 10.20 of 30 | |
| | Number of controlled phases | 3 | |
| | Types of control | Configurable voltage ramp, torque ramp | |
| | Operating cycle | Standard | |
| Functions | | Bypass (intergrated) | |
| Number of I/O | Analog inputs | 1 PTC probe | |
| | Logic inputs | 3 | |
| | Logic outputs | - | |
| | Analog outputs | - | |
| | Relay outputs | 2 | |
| Dialogue | | Integrated display terminal, SoMve Lite setup software | |
| Communication | Integrated | Modbus | |
| Standards and certifications | | IEC/EN 60947-4-2. class A EMC, CE, UL, CSA, C-Tick, GOST, CCC | |
| Motor connection | | Possible to connect the starter in the motor delta connection | |

(1) Possible to connect the starter in the motor delta connection